




HSM SECURIO B32

HSM SECURIO B32

Mobile, high performance model for desktside use. Shreds credit and store cards with ease as well as CDs (details see below). Folding safety element, in the security levels 2 and 3 with infeed slot for CDs. Multi-function operating button and reversing button. Auto-reverse in the event of a paper jam. Economic energy management (EMCS). Quiet operating sound. Filling level display through inspection window. With removable, reusable waste bag. Special CD waste bag for correctly sorted separation of the shredded material. Made in Germany.

| Product type description | SECURIO B32 3,9mm | SECURIO B32 1,9x15mm |
|--|---|--|
| Order number | 1820111 | 1822111 |
| EAN Code | 4026631025096 | 4026631025119 |
| Shredder material |  |  |
| Cutting type | strip cut | particle cut |
| Security level new (DIN 66399) | P-2 / O-2 / T-2 / E-2 | P-5 / T-5 / E-4 / F-2 |
| Security level old (DIN 32757-1) | 2 | 4 |
| Cutting width | 3.9 mm | 1.9 mm |
| Particle length | | 15,00 mm |
| Cutting capacity (70g/m ²) | 22 - 24 sheet | 11 - 13 sheet |
| Cutting capacity (80g/m ²) | 19 - 21 sheet | 9 - 11 sheet |
| Intake width | 310 mm | 310 mm |
| Container volume | 82 l | 82 l |
| Cutting speed | 65 mm/s | 65 mm/s |
| Noise level (idle operation) | 56 dB | 56 dB |
| eclass 5.1 | 24320703 | 24320703 |
| UN/SPSC | 44101603 | 44101603 |
| Power consumption of the motor | 500 W | 500 W |
| Voltage | 230 V | 230 V |
| Frequency | 50 Hz | 50 Hz |
| Warranty period (months) | 24 | 24 |
| Depth | 398 mm | 398 mm |
| Width | 497 mm | 497 mm |
| Height | 793 mm | 793 mm |
| Weight | 25.5 kg | 27 kg |

HSM SECURIO B32

| | |
|--|---|
| Product type description | SECURIO B32 4,5x30mm |
| Order number | 1823111 |
| EAN Code | 4026631025126 |
| Shredder material |  |
| Cutting type | particle cut |
| Security level new (DIN 66399) | P-4 / O-3 / T-4 / E-3 |
| Security level old (DIN 32757-1) | 3 |
| Cutting width | 4.5 mm |
| Particle length | 30,00 mm |
| Cutting capacity (70g/m ²) | 17 - 19 sheet |
| Cutting capacity (80g/m ²) | 14 - 16 sheet |
| Intake width | 310 mm |
| Container volume | 82 l |
| Cutting speed | 65 mm/s |
| Noise level (idle operation) | 56 dB |
| eclass 5.1 | 24320703 |
| UN/SPSC | 44101603 |
| Power consumption of the motor | 500 W |
| Voltage | 230 V |
| Frequency | 50 Hz |
| Warranty period (months) | 24 |
| Depth | 398 mm |
| Width | 497 mm |
| Height | 793 mm |
| Weight | 27 kg |