







## **HSM SECURIO P40**

## HSM SECURIO P40

Mobile, very high performance model for open-plan offices. Multi-function operating button, reversing button and integrated button lock. Auto-reverse in the event of a paper jam. Folding safety element with contact protection and integrated service flap. Automatic oiler for cutting unit (particle cut version only). Separate CD cutting unit (security level 3) and metal detection, depending on security level. Economic energy management (EMCS). Filling level display through inspection window. Large collection volume. With removable, reusable waste bag. Special CD waste container for correctly sorted separation of the shredded material (optional). Made in Germany.

Product type description	SECURIO P40 3,9 mm	SECURIO P40 5,8 mm
Order number	1880111	1881111
EAN Code	4026631031837	4026631031820
Shredder material		
Cutting type	strip cut	strip cut
Security level new (DIN 66399)	P-2 / O-2 / T-2 / E-2	P-2 / O-2 / T-2 / E-2
Security level old (DIN 32757-1)	2	2
Cutting width	3.9 mm	5.8 mm
Particle length		
Cutting capacity (70g/m <sup>2</sup> )	45-47 sheet	58-60 sheet
Cutting capacity (80g/m <sup>2</sup> )	40-42 sheet	51-53 sheet
Intake width	330 mm	330 mm
Container volume	145 l	145 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	59 dB	59 dB
class 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2100 W	2100 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Depth	550 mm	550 mm
Width	580 mm	580 mm
Height	936 mm	936 mm
Weight	67 kg	67 kg

**HSM SECURIO P40**

Product type description	SECURIO P40 4,5x30 mm	SECURIO P40 1,9x15 mm
Order number	1883111	1882111
EAN Code	4026631031844	4026631031851
Shredder material		
Cutting type	particle cut	particle cut
Security level new (DIN 66399)	P-4 / O-3 / T-4 / E-3	P-5 / O-4 / T-5 / E-4
Security level old (DIN 32757-1)	3	4
Cutting width	4.5 mm	1.9 mm
Particle length	30,00 mm	15,00 mm
Cutting capacity (70g/m <sup>2</sup> )	35-37 sheet	22-24 sheet
Cutting capacity (80g/m <sup>2</sup> )	31-33 sheet	18-20 sheet
Intake width	330 mm	330 mm
Container volume	145 l	145 l
Cutting speed	110 mm/s	110 mm/s
Noise level (idle operation)	59 dB	59 dB
eclass 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2100 W	2100 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Depth	550 mm	550 mm
Width	580 mm	580 mm
Height	936 mm	936 mm
Weight	72 kg	72 kg