






## ***HSM SECURIO P44***

## HSM SECURIO P44

Mobile, highest performance model for open-plan offices. Multi-function operating button, reversing button and integrated button lock. Auto-reverse in the event of a paper jam. Folding safety element with contact protection and integrated service flap. Automatic oiler for cutting unit (particle cut version only). Separate CD cutting unit (security level 3) and metal detection, depending on security level. Economic energy management (EMCS). Integrated PAPERcontrol function prevents paper jams. Filling level display through inspection window. Large collection volume. With removable, reusable waste bag. Special CD waste container for correctly sorted separation of the shredded material (optional). Made in Germany.

Product type description	SECURIO P44 5,8 mm	SECURIO P44 3,9x40 mm
Order number	1871111	1873111
EAN Code	4026631032025	4026631032049
Shredder material		
Cutting type	strip cut	particle cut
Security level	2	3
Cutting width	5.8 mm	3.9 mm
Particle length		40,00 mm
Cutting capacity (70g/m <sup>2</sup> )	76-78 sheet	43-46 sheet
Cutting capacity (80g/m <sup>2</sup> )	70-72 sheet	39-41 sheet
Intake width	400 mm	400 mm
Container volume	205 l	205 l
Cutting speed	100 mm/s	100 mm/s
Noise level (idle operation)	66 dB	67 dB
Noise level (full load)	64 dB	65 dB
eclass 5.1	24320704	24320704
UN/SPSC	44101603	44101603
Power consumption of the motor	2600 W	2600 W
Voltage	230 V	230 V
Frequency	50 Hz	50 Hz
Warranty period (months)	24	24
Depth	592 mm	592 mm
Width	700 mm	700 mm
Height	1025 mm	1025 mm
Weight	105 kg	105 kg

**HSM SECURIO P44**

Product type description	SECURIO P44 1,9x15 mm
Order number	1872111
EAN Code	4026631032056
Shredder material	
Cutting type	particle cut
Security level	4
Cutting width	1.9 mm
Particle length	15,00 mm
Cutting capacity (70g/m <sup>2</sup> )	28-30 sheet
Cutting capacity (80g/m <sup>2</sup> )	23-25 sheet
Intake width	400 mm
Container volume	205 l
Cutting speed	100 mm/s
Noise level (idle operation)	66 dB
Noise level (full load)	64 dB
eclass 5.1	24320704
UN/SPSC	44101603
Power consumption of the motor	2600 W
Voltage	230 V
Frequency	50 Hz
Warranty period (months)	24
Depth	592 mm
Width	700 mm
Height	1025 mm
Weight	105 kg